

CHAINWAY®



C60

Mobile Computer



Android



4G



WiFi



Bluetooth



1D Barcode



2D Barcode



NFC



Camera



GPS

Chainway C60 is a lightweight, high-performance, rugged mobile computer for enterprises. C60 is based on Android 10, adopting Qualcomm high-performance processor and high-capacity removable battery with high-end configuration. The computer can integrate functions such as barcodes, NFC, front and rear cameras, etc. The device can be implemented in a wide range of industries, including logistics, warehousing, retail, and asset management, helping clients significantly bring their operations and management to the next level.



Specification

Physical Characteristics

Dimensions	159.5 x 65.7 x 16.8 mm / 6.28 x 2.58 x 0.66 in.
Weight	219 g / 7.72 oz. (device with battery)
Keypad	5 side keys : power, 2 scan keys, volume +/- Main keyboard: 22 keys (numeric keys, direction key, screen-lock key, Enter, Del, F1-F10, etc.)
Battery	4350 mAh removable main battery Standby: up to 490 hours (only main battery ; WiFi: up to 470h; 4G: up to 440h) Continuous use: over 12 hours (depending on user environment) Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Display	4-inch (18:9), TFT α-Si 1080 x 540
Touch Panel	Multi-touch panel, gloves and wet hands supported
Sensor	Accelerometer sensor, light sensor, proximity sensor, gyroscope
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; receiver
Card slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB Type-C, USB 2.0, OTG

Performance

CPU	Qualcomm 1.8GHz Octa-core
RAM+ROM	3 GB + 32 GB 4 GB + 64 GB (optional)
Expansion	Supports up to 128 GB Micro SD card

Developing Environment

Operating System	Android 10; Soti MobiControl, SafeUEM supported
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.92 ft. drops to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication

WWAN	Support 802.11 a/b/g/n/ac/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6, 5G PA; Fast roaming: PMKID caching, 802.11r, OKC Operating Channels: 2.4G(channel 1~13), 5G(channel36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132,136,140,144,149,153,157,161,165).Depends on local regulations Security and Encryption: WEP/WPA/WPA2-PSK(TKIP and AES),WAPI-PSK—EAP-TTLS,EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS,PEAP-GTC,etc.
-------------	--

WWAN	2G: 850/900/1800/1900 MHz 3G: CDMA EVDO: BCO, BC1 WCDMA: B1/B2/B4/B5/B8 TD-SCDMA: A/F(B34/B39) 4G: B1/B2/B3/B4/B5/B7/B8/B12/B13/B17/B20/B28/B38/B39/B40/B41
Vo-LTE	Support Vo-LTE HD video voice call
Bluetooth	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
GNSS	GPS/AGPS, GLONASS, BeiDou,Galileo,internal antenna

Data Collection

Camera

Front Camera	5MP
Rear Camera	Rear 13MP Autofocus with flash

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

Barcode Scanning (optional)

2D Scanner	Zebra: SE4710; Honeywell: N6603; DS7000, IA166S, IA171S
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX),etc.

Optional accessories(See details in Accessory Guide)

Wrist Strap; Rubber Bumper; Charging Cradle

Notice: Product specifications are subject to change without prior notice. / Model: C60 / Update Date: 2022-05-09

CHAINWAY[®]

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net